



technical specifications

VK-IPC-T351-ZAS-I



5 MP
2.7 mm – 13.5 mm



built-in IR LED
40 m



perimeter protection
face detection
SMD



IP67
metal case

Camera

Image sensor	1/2.7" CMOS
Max. resolution	5MP, 2880 (H) x 1620 (V)
ROM	128 MB
RAM	256 MB
Electronic shutter	Auto/Manual 1/3 s - 1/1000000 s
Min. illumination	0.002 Lux (Color) 0.0002 Lux (B/W) 0 Lux (Illuminator on)
S/N Ratio	> 56 dB
Illumination distance	IR distance 40 m
Illuminator control	Auto/Manual

Motion detection	OFF/ON (4 areas, rectangular)
Noise reduction	3D NR
Image rotation	0°/90°/180°/270°
Mirror	Yes
Privacy masking	4 areas

Intelligence

Smart motion detection	Yes
Perimeter protection	Intrusion, tripwire (Support the classification of Vehicle / Human / Non-Motor)
Face detection	Yes
AI search	Works together with NVR

Lens

Lens type	Motorized vari-focal
Focal length	2.7 mm – 13.5 mm
Max. aperture	F/1.6
Field of view	H: 108° – 33° / V: 57° – 18° / D: 129° – 37°
Iris type	Auto

Audio

Built-in mic	Yes
Built-in speaker	Yes
Audio compression	G.711a/G.711Mu/G.726/G.726ASF

Video

Compression	H.264H/H.264M/H.264B/H.265
Smart compression	H.264H+/H.264M+/H.264B+/H.265+
Video frame rate	Main Stream: 5MP (1 fps–25/30 fps) Sub Stream: D1 (1 fps–25/30 fps) Third Stream: 720P (1 fps–25/30 fps)
Bit rate control	CBR/VBR
Video bit rate	H.264: 3 Kbps–20480 Kbps H.265: 3 Kbps–20480 Kbps
Day/Night	Color/B/W
BLC	Yes
HLC	Yes
AWB	Yes
AGC	Auto/Manual
WDR	140 dB

Alarm



Sound alarm	Yes
Alarm event	network disconnection; IP conflict, no SD card, capacity warning, SD card error

Network

Network	RJ-45 (10/100 Base-T)
SDK and API	Yes
Network protocol	TCP/IP, UDP, HTTP, IGMP, ICMP, DHCP, RTP/RTSP, DNS, DDNS, FTP, NTP, PPPOE, UPNP, SMTP
Interoperability	ONVIF, CGI, P2P
User/Host	20 (total bandwidth: 80 M)
Storage	FTP, micro SD card (support max. 256G)
Browser	IE8 and later Chrome Firefox

General

Power supply	12V DC ($\pm 30\%$) / PoE (802.3af)
Power consumption	Basic: 2.5W / Max.: 6.2W
Operating conditions	-30°C to $+60^{\circ}\text{C}$ / Less than 95% RH
Storage conditions	-40°C to $+60^{\circ}\text{C}$
Protection grade	IP67
Casing	Metal
Dimensions	110 mm \times $\phi 122$ mm



Available models:
 VK-IPC-T351-ZAS-I
 VK-IPC-T351-ZAS-I-B