

## technical specifications

# VK-NVR2104-4P-C



4 CH, 4 PoE ports  
up to 4K



perimeter protection  
face detection  
human / vehicle detection



1 HDD  
up to 14 TB



HDMI up to 4K  
audio 1 input / 1 output

### System

OS	Embedded Linux
OS operation interface	Web/operating in local GUI

### AI by camera

Perimeter protection	Yes, 4 channels
Face detection	Yes, 4 channels
Human/vehicle detection	Yes, 4 channels
SMD	Yes, 4 channels

### Bandwidth

Incoming	80Mbps
Outcoming	80Mbps
IPC input	4CH
IPC access	Support one-click add IPC function

### Video & audio output

VGA	1080P / 1.3MP / 720P
HDMI	4K / 1080P / 1.3MP / 720P
Audio output	1CH, RCA (line out, 2Vp-p)

### Audio

Audio compression	G.711A
Audio bit rate	8Kbps (16bit)
Two-way talk	Yes

### Video & audio decoding

IP channel resolution	Up to 3840 x 2160
Video decoding	H.265 / H.264
Audio decoding	G.711A / G711U / G726
Synchronous playback	4CH
Decoding ability	4CH 1080P@30fps / 1CH 4K@30fps

### Preview & playback

Synchronous preview	4
Multi-screen display	1, 4 views
Record mode	Manual; schedule (general; MD; alarm; intelligent)
AI search	Search by target classification (human, vehicle, non-motor vehicle)
Backup	USB device
Playback function	1. Play; pause; stop; fast forward; fast backward; rewind; play by frame 2. Full screen; backup (cut/file); partially enlarge; audio on/off

### Alarm linkage

Record; snapshot; buzzer; log; preset; email

### Network

Network protocol	HTTP; TCP/IP; IPv4; UPnP; SNMP; RTSP; UDP; SMTP; NTP; DHCP; DNS; IP Filter; DDNS; FTP; P2P; Auto register
Mobile	Android; iOS
Interoperability	ONVIF; SDK
Browser	IE8 or later

### HDD

SATA	1
Max capacity	14TB

### External interface

Network	1 RJ-45 100M
VGA	1
HDMI	1
USB	2 x 2.0
PoE ports	4
Audio i / o	1 / 1

## General

Front panel	C
Dimensions	Mini 1U 215 x 235 x 45 mm
Installation	Desktop installation
Power supply	DC 48V / 1.35A
Consumption	7W (without HDD/PoE)
Working temperature	-10°C to +55°C
Working humidity	10% ~ 90%

